

MAG2450 Dante Active Wall-Mounted Speaker



Features

- Dual network interface design, hand-in-hand connection
- Built in 2X25W digital power amplifier
- Two Aux Input,two Aux output and one microphone input;
- Mic with priority and mute function
- Volume could be adjusted
- Black and White Color available
- Power Supply AC220V/50Hz

Description

MAG2450 is a high-fidelity speaker with LAN digital audio transmission technology and Bluetooth function. It adopts dual network interface design, and support hand-in-hand connection. There are 2 AUX IN for other audio source devices (like DVD), 2 AUX OUT for other amplifiers to increase the power and 1 MIC IN for local paging and so on.

Specification

Model	MAG2450
Rated Output Power	25W
AUX Level	1000(±100)mV
MIN. EMF.	MIC: 5.5±0.5mV (Unbalanced)
	LINE: 300±50mV (Unbalanced)
Frequency Response	MIC: 50Hz-16kHz (±3dB) LINE: 20Hz-20kHz (±3dB)
THD	≤1% (1kHz, under normal working condition)
SNR	MIC IN: ≥ 65dB LINE IN: ≥ 70dB
Protection	AC fuse, over current, over heat, over voltage, under voltage, overload, and short circuit.
Mute Function	MIC IN will override other inputs.
Power Supply	AC 220V/50Hz
Rated Power Consumption	≤100W
Outer Dimension (mm)	(L×W×H) 590×275×390
Machine Dimension (mm)	(L×W×H) 310×215×200
Gross Weight	11kg (2 pieces)
Net Weight	4kg